

ANT-IMG11 Series

Introduction

ANT-IMG11 series is a 10/100/1000Base adaptive managed fiber-optic transceiver, with a Gigabit optical port, a 10/100/1000Base-T(X) adaptive Ethernet port. Product design in line with Ethernet standards, add lightning protection, anti-static protection measures, -20?-70wide range of operating temperature, stable and reliable performance. The network management interface of this device is simple and functional.

Support a variety of network management, including SNMP, WEB, Console and Telnet and other network management methods, can achieve the centralized network management rack. The device can be widely used in safe city, rail transportation, operator network construction and other projects.

Features

- Compliance with IEEE 802.3, IEEE 802.3U, IEEE 802.3X, IEEE 802.1Q, IEEE 802.3AB, 10Base-TX, 100Base-TX, 1000Base-TX, 1000Base-FX standards.
- Uses the high-performance chip, realizes the non-blocking transmission exchange performance, guarantees the data transmission to have higher security and the stability.
- Support 10/100/1000M, full/half-duplex adaptive/forced function. Auto-MDI / MDIX auto-flip.
- Support SC, FC, ST connectors (1*9 modules) and SFP transceiver modules.
- Provide status indicators, built-in power supply (AC 110-220V / DC 48-110V).
- Support 850nm, 1310nm, 1550nm and the DWDM/CWDM wavelength specified by ITUT.
- Support loop-speed loopback, easy line debugging.
- Support LFP function, can quickly locate the link where the fault occurs.
- Support remote power failure alarm.
- The Inband Management feature supports both 802.3ah and TS1000. Powerful network management function, support WEB mode and simple network management protocol SNMP network management mode.
- Support hot-plug simple to install, the status indicator is complete, working status at a glance.
- Supports 2U racks (16 channels) and stand-alone racks. Stand-alone desktop built-in professional communications power, support dual power supply redundancy (support OLP function).

Specification

Protocol Standard	IEEE 802.3, IEEE 802.3u, IEEE 802.3 Flow control, IEEE 802.1q VLAN, IEEE 802.1p QoS, IEEE 802.1ad Q-in Q VLAN, TS-1000
Wavelength	850nm/1310nm/1550nm

Transmission Distance	Cat5 100m Multimode, Dual-fiber 550m Single Mode, Dual-fiber 20/40/60/80/100/120Km
Ethernet Port	RJ45 Ports, Connection STP / UTP Cat5/Cat5e Cooper Cable
Fiber Port	Multimode, Dual-fiber SC/FC/ST/LC (Diameter 50/125, 62.5 / 125?m) Single Mode, Dual-fiber SC/FC/ST/LC (diameter 9/125?m)
Exchange Attribute	Conversion Method: Media conversion, store and forward / straight in MAC Add: 1 K page 2 / 3 Cache: 512 Kbit Full duplex state: flow control, half-duplex: backpressure mode Store and Forward: 9.6us, Straight In: 0.9us BER:<1/1000000000
LED Indicator	PWR (Power Supply) FX LINK/ACT (Optical fiber port connection) LFP (LFP function working) TX LINK/ACT (Ethernet port connection) TX SPD (Ethernet port speed indicate) TX DUP (Ethernet port full duplex mode)
Power Supply	Power Input: AC 110-220V / DC 48-110V Full Load:<4 W
Working Environment	Operating Temperature: -20~70? Storage Temperature: -40~70? Storage Humidity: 5% to 90% non-condensing
Dimension	156*128*32mm (L * W * H)
Certification	CE, FCC, RoHS
Warranty	3-years

Order Information

Model No.	Description of Goods
ANT-IMG11	10/100/1000M Multimode, Dual Fiber, 550m, SC/ST/FC/LC Connector
ANT-IMG11-20/40/60/80 /100	10/100/1000M Single-mode, Dual Fiber, 20/40/60/80/100Km, SC/ST/FC/LC Connector
ANT-IMG11W-20/40/60/ 80/100	10/100/1000M Single-mode, Dual Fiber, 20/40/60/80/100Km, SC/ST/FC/LC Connector